

口径		厚み		1.2mm		1.5mm		2.0mm		2.5mm	
呼び径	外径(mm)	厚み	価格	厚み	価格	厚み	価格	厚み	価格	厚み	価格
6A	10.5										
8A	13.8	1.2	7,960	1.5	9,590	2.0	12,110				
10A	17.3	1.2	8,730	1.5	10,370	2.0	12,660				
15A	21.7	1.2	10,390	1.5	12,350	2.0	14,850	2.5	17,310		
20A	27.2	1.2	12,720	1.5	15,130	2.0	18,020	2.5	21,090		
25A	34.0	1.2	15,560	1.5	18,330	2.0	21,780	2.5	26,130		
32A	42.7	1.2	19,540	1.5	22,400	2.0	27,560	2.5	32,730		
40A	48.6	1.2	22,200	1.5	25,170	2.0	30,650	2.5	36,590		
50A	60.5			1.5	30,930	2.0	37,960	2.5	45,820		
65A	76.3					2.0	47,990	2.5	57,990		
80A	89.1					2.0	56,420	2.5	68,070		
100A	114.3					2.0	73,310	2.5	88,450		
125A	139.8										
150A	165.2										

口径		厚み		3.0mm		3.5mm		4.0mm		5.0mm	
呼び径	外径(mm)	厚み	価格	厚み	価格	厚み	価格	厚み	価格	厚み	価格
8A	13.8										
10A	17.3	3.0	17,250								
15A	21.7	3.0	19,350								
20A	27.2	3.0	23,690								
25A	34.0	3.0	29,250	3.5	34,370	4.0	38,910				
32A	42.7	3.0	37,140	3.5	44,010	4.0	49,470				
40A	48.6	3.0	41,210	3.5	49,000	4.0	55,560				
50A	60.5	3.0	52,120	3.5	60,300	4.0	68,180	5.0	87,820		
65A	76.3	3.0	66,360	3.5	76,970	4.0	87,270	5.0	112,190		
80A	89.1	3.0	77,880	3.5	90,300	4.0	102,730	5.0	132,360		
100A	114.3	3.0	100,910	3.5	116,970	4.0	133,330	5.0	169,790		
125A	139.8	3.0	126,110	3.5	145,680	4.0	165,270	5.0	207,710		
150A	165.2	3.0	149,600	3.5	172,620	4.0	197,100	5.0	247,270		
200A	216.3	3.0	198,510	3.5	229,960	4.0	262,110	5.0	324,550		
250A	267.4	3.0	259,200	3.5	298,300	4.0	340,450	5.0	424,760		
300A	318.5	3.0	311,810	3.5	360,000	4.0	409,090	5.0	510,550		

口径		厚み		6.0mm		6.5mm		8.0mm		8.1~10.9mm	
呼び径	外径(mm)	厚み	価格	厚み	価格	厚み	価格	厚み	価格	厚み	価格
40A	48.6										
50A	60.5										
65A	76.3	6.0	133,640								
80A	89.1	6.0	157,820								
100A	114.3	6.0	202,250								
125A	139.8	6.0	249,700								
150A	165.2	6.0	297,140							7.1	339,400
200A	216.3	6.0	393,270	6.5	436,850	8.0	533,210	8.2	577,000		
250A	267.4	6.0	505,820	6.5	563,400	8.0	690,000	9.3	855,000		
300A	318.5	6.0	612,000	6.5	673,400	8.0	826,670	10.3	1,130,000		

定尺4m (単位: 円/本)

配管用ステンレス鋼管 (JIS-G3459)

SUS304 ステンレスパイプエキストラ・1本当り重量表

呼び径		外径 (mm)	厚 さ (mm)																							
A	B		1.2		1.5		2.0		2.5		3.0		3.5		4.0		5.0		6.0		6.5					
		円	kg	円	kg	円	kg	円	kg	円	kg	円	kg	円	kg	円	kg	円	kg	円	kg	円	kg			
8	1/4	13.8	740	1.51	720	1.84	700	2.35																		
10	3/8	17.3	500	1.92	450	2.36	370	3.05	330	3.69	330	4.28														
15	1/2	21.7	400	2.45	350	3.02	250	3.92	190	4.80	140	5.60														
20	3/4	27.2	350	3.11	300	3.84	180	5.04	130	6.16	80	7.24														
25	1	34.0	310	3.92	250	4.84	130	6.36	100	7.84	40	9.28	70	10.6	70	12.0										
32	1 1/4	42.7	300	4.96	200	6.16	120	8.12	80	10.00	30	11.90	60	13.7	60	15.4										
40	1 1/2	48.6	290	5.68	180	7.04	90	9.28	50	11.50	ベース	13.60	30	15.7	30	17.8										
50	2	60.5			160	8.80	80	11.60	50	14.40	ベース	17.20	ベース	19.9	ベース	22.5	50	27.6								
65	2 1/2	76.3					70	14.80	40	18.40	ベース	21.90	ベース	25.4	ベース	28.8	40	35.6	50	42.0						
80	3	89.1					70	17.40	40	21.60	ベース	25.70	ベース	29.8	ベース	33.9	40	42.0	50	49.6						
90	3 1/2	101.6					80	19.80	50	24.70	ベース	29.50	ベース	34.2	ベース	38.9	30	48.0	50	57.2						
100	4	114.3					80	22.40	50	27.80	ベース	33.30	ベース	38.6	ベース	44.0	30	54.4	30	64.8						
125	5	139.8					150	27.50	80	34.20	20	40.80	10	47.6	10	54.0	20	67.2	30	80.0						
150	6	165.2									20	48.40	10	56.4	10	64.4	20	80.0	30	95.2						
200	8	216.3									30	63.60	20	74.4	20	84.8	20	105.0	30	126.0	60	136.0				
250	10	267.4									80	79.20	70	92.0	70	105.0	70	131.0	70	156.0	100	169.0				
300	12	318.5									90	94.40	80	110.0	80	125.0	80	156.0	80	187.0	100	202.0				

1本当たり価格 = (相場(ベース) + エキストラ) × 重量

定尺4m (単位: 円/kg・kg/本)

ステンレスパイプの肉厚(mm)・スケジュール別

呼び径	A	6	8	10	15	20	25	32	40	50	65	80	90	100	125	150	200	250	300
	B	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	3 1/2	4	5	6	8	10	12
SCH5		1.0	1.2	1.2	1.5	1.5	2.0	2.0	2.0	2.0	2.0	2.0	2.5	2.5	3.0	3.0	3.0	3.5	4.0
SCH10		1.2	1.5	2.0	2.0	2.0	2.5	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.5	3.5	4.0	4.0	4.5
SCH20		1.5	2.0	2.0	2.5	2.5	3.0	3.0	3.0	3.5	3.5	4.0	4.0	4.0	5.0	5.0	6.5	6.5	6.5
SCH40		2.0	2.5	2.5	3.0	3.0	3.5	3.5	4.0	4.0	5.0	5.5	6.0	6.0	6.6	7.1	8.2	9.3	10.3
SCH80		2.5	3.0	3.5	3.5	4.0	4.5	5.0	5.0	5.5	7.0	8.0	8.0	9.0	10.0	12.0	13.0	15.0	18.0

※表はSP懇話会慣用標準寸法です。

25A (SCH10) の肉厚については3.0 (mm) を用いる場合もございます。

【改定 2019.12】